


LED TRACK LIGHT

BLACK



| caption                     | the value      |
|-----------------------------|----------------|
| Rated wattage               | 40 w           |
| Rated current               | <b>0.4 A</b>   |
| Rated voltage               | 220-240 V      |
| Power Factor                | 50/60 Hz       |
| Displacement Factor         | <b>0.9</b>     |
| Rated lumens                | <b>3800 Lm</b> |
| Efficiency                  | <b>95 Lm/w</b> |
| Lumen Maintenance           | 6000 h         |
| Beam Angle                  | 24°            |
| Color temperature           | 4000 k         |
| Consistency sdcm            | <b>&lt; 6</b>  |
| CRI                         | >80            |
| Rated Lifetime              | 30000 h        |
| Switch cycle                | 15000          |
| Ta                          | 40 °c          |
| Safety Standard             | IEC 60598      |
| Electrical Class            | II             |
| IP rating                   | 20             |
| EMC                         | /              |
| EMF                         | /              |
| EMI                         | /              |
| Cutout                      | <b>90 mm</b>   |
| Width                       | 160 mm         |
| Height                      | 180 mm         |
| Weight                      | 00 g           |
| Dimming                     | No             |
| Main Color of the luminaire | BLACK          |
| Color impact code (IK)      | 02             |

Super protection:

It is made of very safe materials, so it is environmentally friendly

Provides flexibility in installation and ease of installation

LED CHIP: SANAN SMD 3030



Photometric curve

