

Model No:103053





Super protection:
It is made of very safe materials,
so it is environmentally friendly
Provides flexibility in installation
and ease of installation.
LED by: **CTO**



Caption	Value
Rated wattage	30 w
Rated current	0.217 A
Rated voltage	220-240V
Power Factor	50/60 Hz
Displacement Factor	0.9
Rated lumens	2400 Lm
Efficiency	80 Lm/w
Lumen Maintenance	6000 h
Beam Angle	<120°
Color temperature	3000 K
Consistency sdcm	<6
CRI	>80
Rated Lifetime	20000 h
Switch cycle	15000
Ta	25 °c
Safety Standard	IEC 60598
Electrical Class	I
IP rating	20
EMC	/
EMF	/
EMI	/
Length	200 ϕ
Width	230x55.5 mm
Height	225 mm
Weight	0.5 Kg
Dimming	No
Main Color of the luminaire	White
Color impact code (IK)	02

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



Applications:

- Restaurant ,Shopping
- Mall ,Hotel ,Home

Features:

- Longevity beautiful, comfortable light ultra- efficient led lighting
- Key features:
- 80% energy savings
- Eco-friendly.

ENERGY SAVING

LIFETIME 20000 H