

LED Spot Downlight
Anti-glare
RECESSED 90*47mm
moving



WHITE/BLACK

Usage: Spotlight lighting for lighting interior ceilings perfectly, which is suitable for gypsum and concrete lamps, so it can be placed in rooms of the house, companies, or hotels.



| caption | the value |
|-----------------------------|---------------|
| Rated wattage | 7 w |
| Rated current | 55-107 mA |
| Rated voltage | 100-240 V |
| Power Factor | 50/60 Hz |
| Displacement Factor | 0.7 |
| Rated lumens | 525 Lm |
| Efficiency | 75 Lm/w |
| Lumen Maintenance | 6000 h |
| Beam Angle | 38° |
| Color temperature | 3000 k |
| Consistency sdcn | < 6 |
| CRI | > 80 |
| Rated Lifetime | 15000 h |
| Switch cycle | 7500 |
| Ta | 40 °c |
| Safety Standard | IEC 60548 |
| Electrical Class | II |
| IP rating | 20 |
| EMC | / |
| EMF | / |
| EMI | / |
| Cutout | 70 |
| Width | 90 mm |
| Height | 47 mm |
| Weight | 0.065 kg |
| Dimming | No |
| Main Color of the luminaire | WHITE / BLACK |
| Color impact code (IK) | 02 |

