



## **BLACK**

Rated wattage       20 w         Rated current       0.170 A         Rated voltage       170 - 240         Line Frequency       50/60Hz         Displacement Factor       ≥ 0.7         Rated lumens       1600 Lm         Efficacy       80 Lm/w         Lumen Maintenance       6000 h         Beam Angle       ≥ 120°         Color temperature       3000k         Consistency sdcm       < 6         CRI       ≥ 80         Rated Lifetime       25000 h         Switch cycle       12500         Ta       -20 ~ 40 °c         Safety Standard       IEC 60598         Electrical Class       II         IP rating       65         EMC       /         EMF       /         EMI       /         Length       46 mm         Width       135 mm         Height       265 mm         Weight       0.8 Kg         Dimming       No         Main Color of the luminaire       BLACK	caption	the value
Rated voltage  Line Frequency  Displacement Factor  Rated lumens  Efficacy  Lumen Maintenance  6000 h  Beam Angle  Color temperature  Consistency sdcm  CRI  Rated Lifetime  Switch cycle  Ta  -20 ~ 40 °c  Safety Standard  Electrical Class  IP rating  EMC  EMF  EMC  Length  Width  Height  Weight  Displacement Factor  50/60Hz  50/60Hz  50/60Hz  6000 h  80 Lm/w  80 Lm/w  80 Lm/w  80 Lm/w  80 Lm/w  80 Lm/w  1600 h  8000 h  2120°  220°  240° c  53000 h  12500  Ta  -20 ~ 40° c  53fety Standard  IEC 60598  Electrical Class  II  IP rating  65  EMC  /  EMF  /  EMI  Length  46 mm  Width  135 mm  Height  O.8 Kg  Dimming  No  Main Color of the luminaire	Rated wattage	<b>20</b> w
Line Frequency  Displacement Factor  Rated lumens  Efficacy  Boom Angle  Color temperature  Consistency sdcm  CRI  Rated Lifetime  Switch cycle  Ta  Safety Standard  Electrical Class  IP rating  EMC  EMF  EMI  Length  Width  Height  Weight  Dimming  Main Color of the luminaire  ≥ 0.7  80 Lm/w  120°  Coop 120°	Rated current	0.170 A
Displacement Factor  Rated lumens  Efficacy  Bo Lm/w  Lumen Maintenance  6000 h  Beam Angle  Color temperature  3000k  Consistency sdcm  CRI  Rated Lifetime  25000 h  Switch cycle  12500  Ta  -20 ~ 40 °c  Safety Standard  IEC 60598  Electrical Class  II  IP rating  65  EMC  /  EMF  /  EMI  Length  Width  135 mm  Height  Weight  0.8 Kg  Dimming  No  Main Color of the luminaire	Rated voltage	170 - 240
Rated lumens1600 LmEfficacy80 Lm/wLumen Maintenance6000 hBeam Angle≥ 120°Color temperature3000kConsistency sdcm< 6	Line Frequency	50/60Hz
Efficacy 80 Lm/w  Lumen Maintenance 6000 h  Beam Angle ≥ 120°  Color temperature 3000k  Consistency sdcm < 6  CRI ≥ 80  Rated Lifetime 25000 h  Switch cycle 12500  Ta -20 ~ 40 °c  Safety Standard IEC 60598  Electrical Class II  IP rating 65  EMC /  EMF /  EMI /  Length 46 mm  Width 135 mm  Height 265 mm  Weight 0.8 Kg  Dimming No  Main Color of the luminaire BLACK	Displacement Factor	≥ 0.7
Lumen Maintenance6000 hBeam Angle≥ 120°Color temperature3000kConsistency sdcm< 6	Rated lumens	1600 Lm
Beam Angle  Color temperature  3000k  Consistency sdcm  < 6  CRI  ≥ 80  Rated Lifetime  25000 h  Switch cycle  12500  Ta  -20 ~ 40 °c  Safety Standard  IEC 60598  Electrical Class  II  IP rating  65  EMC  / EMF  // EMI  Length  46 mm  Width  135 mm  Height  Weight  0.8 Kg  Dimming  No  Main Color of the luminaire  BLACK	Efficacy	80 Lm/w
Color temperature 3000k  Consistency sdcm < 6  CRI ≥ 80  Rated Lifetime 25000 h  Switch cycle 12500  Ta -20 ~ 40 °c  Safety Standard IEC 60598  Electrical Class II  IP rating 65  EMC /  EMF /  EMI /  Length 46 mm  Width 135 mm  Height 265 mm  Weight 0.8 Kg  Dimming No  Main Color of the luminaire BLACK	Lumen Maintenance	6000 h
Consistency sdcm < 6  CRI ≥ 80  Rated Lifetime 25000 h  Switch cycle 12500  Ta -20 ~ 40 °c  Safety Standard IEC 60598  Electrical Class II  IP rating 65  EMC /  EMF /  EMI /  Length 46 mm  Width 135 mm  Height 0.8 Kg  Dimming No  Main Color of the luminaire BLACK	Beam Angle	≥ 120°
CRI ≥ 80  Rated Lifetime 25000 h  Switch cycle 12500  Ta -20 ~ 40 °c  Safety Standard IEC 60598  Electrical Class II  IP rating 65  EMC /  EMF /  EMI /  Length 46 mm  Width 135 mm  Height 265 mm  Weight 0.8 Kg  Dimming No  Main Color of the luminaire BLACK	Color temperature	3000k
Rated Lifetime 25000 h  Switch cycle 12500  Ta -20 ~ 40 °c  Safety Standard IEC 60598  Electrical Class II  IP rating 65  EMC /  EMF /  EMI /  Length 46 mm  Width 135 mm  Height 265 mm  Weight 0.8 Kg  Dimming No  Main Color of the luminaire BLACK	Consistency sdcm	< 6
Switch cycle  Ta  -20 ~ 40 °c  Safety Standard  Electrical Class  II  IP rating  65  EMC  /  EMF  /  EMI  Length  Width  135 mm  Height  Weight  Dimming  Main Color of the luminaire  12500  I 12500  12500  140 °c  65  ECC  60598  II  /  I  /  I  /  EC 60598  I  I  I  I  A  65  EMC  /  EMF  /   /  EMF  /  EMI  /  Length  Mo  BLACK	CRI	≥ 80
Ta -20 ~ 40 °c  Safety Standard IEC 60598  Electrical Class II  IP rating 65  EMC /  EMF /  EMI /  Length 46 mm  Width 135 mm  Height 265 mm  Weight 0.8 Kg  Dimming No  Main Color of the luminaire BLACK	Rated Lifetime	25000 h
Safety Standard IEC 60598  Electrical Class II  IP rating 65  EMC /  EMF /  EMI /  Length 46 mm  Width 135 mm  Height 265 mm  Weight 0.8 Kg  Dimming No  Main Color of the luminaire BLACK	Switch cycle	12500
Electrical ClassIIIP rating65EMC/EMF/EMI/Length46 mmWidth135 mmHeight265 mmWeight0.8 KgDimmingNoMain Color of the luminaireBLACK	Та	-20 ~ 40 °c
IP rating 65  EMC /  EMF /  EMI /  Length 46 mm  Width 135 mm  Height 265 mm  Weight 0.8 Kg  Dimming No  Main Color of the luminaire BLACK	Safety Standard	IEC 60598
EMC / EMF / EMI / Length 46 mm Width 135 mm Height 265 mm Weight 0.8 Kg Dimming No Main Color of the luminaire BLACK	Electrical Class	II
EMF / EMI / Length 46 mm Width 135 mm Height 265 mm Weight 0.8 Kg Dimming No Main Color of the luminaire BLACK	IP rating	65
EMI / Length /46 mm Width 135 mm Height 265 mm Weight 0.8 Kg Dimming No Main Color of the luminaire BLACK	EMC	/
Length 46 mm  Width 135 mm  Height 265 mm  Weight 0.8 Kg  Dimming No  Main Color of the luminaire BLACK	EMF	/
Width135 mmHeight265 mmWeight0.8 KgDimmingNoMain Color of the luminaireBLACK	EMI	/
Height 265 mm  Weight 0.8 Kg  Dimming No  Main Color of the luminaire BLACK	Length	46 mm
Weight0.8 KgDimmingNoMain Color of the luminaireBLACK	Width	135 mm
Dimming No Main Color of the luminaire BLACK	Height	265 mm
Main Color of the luminaire BLACK	Weight	0.8 Kg
	Dimming	No
Color impact code (IV)	Main Color of the luminaire	BLACK
Coloi illipact code (IK) U8	Color impact code (IK)	08

## **LED WALL LAMP**

- **Energy Savings**
- 2. Eco-Friendly
- 3. High Brightness
- Flexible Features 4.
- 5. Lights Up Instantly
- 6. Less Heat Dissipation
- 7. Shock-Resistant















Our LED Wall Light is an excellent wall light option for your outdoor illumination needs. With an IP65 rating, 25,000-hour lifespan.

