


## **LED NEWPOWER GU10**





| <del>_</del>                | 49        |
|-----------------------------|-----------|
| caption                     | the value |
| Rated wattage               | 9 w       |
| Rated current               | 50-93m A  |
| Rated voltage               | 100-240 V |
| Power Factor                | 50/60 Hz  |
| Displacement Factor         | 0.5       |
| Rated lumens                | 810 Lm    |
| Efficiency                  | 90 Lm/w   |
| Lumen Maintenance           | 6000 h    |
| Beam Angle                  | 36°       |
| Color temperature           | 2700 k    |
| Consistency sdcm            | <6        |
| CRI                         | >80       |
| Rated Lifetime              | 15000 h   |
| Switch cycle                | 15000     |
| Та                          | -20~45 °c |
| Safety Standard             | IEC 62560 |
| Electrical Class            | II        |
| IP rating                   | 20        |
| EMC                         | /         |
| EMF                         | /         |
| EMI                         | 1         |
| Cutout                      | GU10      |
| Width                       | 50 mm     |
| Height                      | 56 mm     |
| Weight                      | 32 g      |
| Dimming                     | No        |
| Main Color of the luminaire | White     |
| Color impact code (IK)      | 02        |

## **Super protection:**

It is made of very safe materials, so it is environmentally friendly Provides flexibility in installation and ease of installation

















## Areas of application

- Shops and
- exhibition rooms
- Domestic applications
- Commercial applications
- Accent lighting
- Outdoor use in suitable outdoor luminaires only



30 April 2025