



## **LED GARDEN LIGHT**



2. Eco-Friendly

ITEM NO: 106098

- 3. High Brightness
- 4. Flexible Features
- 5. Lights Up Instantly
- 6. Less Heat Dissipation
- 7. Shock-Resistant
- 8. LED Ship CREE \$\(\begin{array}{c} LED \\
  \end{array}









| Rated wattage Rated current  Rated voltage  15 w  Rated voltage  100-240 | .23 A<br>) V<br>z |
|--|-------------------|
| Rated current 0.13 - 0.  Rated voltage 100-240                           | ) V<br>z          |
| Rated voltage 100-240  | ) V<br>z          |
| <del>-</del>   | Z                 |
| Line Fraguency EO/COLL   |                   |
| Line Frequency 50/60Hz   |                   |
| Displacement Factor 0.7  |                   |
| Rated lumens 1425 Lm   |                   |
| Efficiency 95 Lm/v   | V                 |
| Lumen Maintenance 6000 h   |                   |
| Beam Angle 80°   |                   |
| Color temperature 3000 k   |                   |
| Consistency sdcm <6  |                   |
| CRI >80  |                   |
| Rated Lifetime 30000 h   | ı                 |
| Switch cycle 15000   |                   |
| Ta -10 ~ 40  | ) °c              |
| Safety Standard IEC 6059   | 98                |
| Electrical Class   |                   |
| IP rating 65   |                   |
| EMC /  |                   |
| EMF /  |                   |
| EMI /  |                   |
| Length 85 mm   |                   |
| Width 125 mm   | 1                 |
| Height 145 mm  | 1                 |
| Weight 1.2 Kg  |                   |
| Dimming No   |                   |
| Main Color of the luminaire Grey   |                   |

Color impact code (IK)



## COB

08

Model No:GDL-15W-A

## **LED Garden LIGHIT**

It is made of high-quality components, It has a very high degree of protection **IP65**, providing protection against the ingress of dust and water jets.

It shines with light of neutral - the most universal colour .

Narrow beam angle gives directional light so that selected surfaces can be better exposed.

**EACH BOX CONTAINS TWO PIECES**