

## LINEAR WALL WASHER



36W



caption	the value
---------	-----------

Rated wattage	36 w
---------------	------

Rated current	1.46A
---------------	-------

Rated voltage	220-240 V
---------------	-----------

Line Frequency	50/60Hz
----------------	---------

Displacement Factor	>=0.9
---------------------	-------

Rated lumens	3600 Lm
--------------	---------

Efficacy	100 Lm/w
----------	----------

Lumen Maintenance	6000 h
-------------------	--------

Beam Angle	26.5°
------------	-------

Color temperature	3000 k
-------------------	--------

Consistency sdcm	<6
------------------	----

CRI	>80
-----	-----

Rated Lifetime	30000 h
----------------	---------

Switch cycle	15000
--------------	-------

Ta	-10 ~ 40 °c
----	-------------

Safety Standard	IEC 60598-1
-----------------	-------------

Electrical Class	I
------------------	---

IP rating	65
-----------	----

EMC	/
-----	---

EMF	/
-----	---

EMI	/
-----	---

Length	75 mm
--------	-------

Width	50 mm
-------	-------

Height	1000 mm
--------	---------

Weight	0.60 Kg
--------	---------

Dimming	No
---------	----

Main Color of the luminaire	Grey
-----------------------------	------

Color impact code (IK)	04
------------------------	----

### Product Benefits

- Visual comfort with maximum energy saving.
- Minimalist design with optimum performance.
- Quick & simple installation.
- Flexible deployment options with a wide spectrum of applications.



## GREY

Model No:wwl-100cm-36w-SG

### LINEAR WALL WASHER LIGHT

Compact & Minimalist linear surface mounted luminaire designed for wall, ceiling & floor mount application. Ideal light distribution serves both wall washing & wall grazing applications.