

## LINEAR WALL WASHER



36W



### caption

### the value

|                             |             |
|-----------------------------|-------------|
| Rated wattage               | 12 w        |
| Rated current               | 1.46 A      |
| Rated voltage               | 220-240 V   |
| Line Frequency              | 50/60Hz     |
| Displacement Factor         | >0.7        |
| Rated lumens                | 420 Lm      |
| Efficacy                    | 35 Lm/w     |
| Lumen Maintenance           | 6000 h      |
| Beam Angle                  | 26.5°       |
| Color temperature           | RGB         |
| Consistency sdcn            | <6          |
| CRI                         | >80         |
| Rated Lifetime              | 30000 h     |
| Switch cycle                | 15000       |
| Ta                          | -10~40°C    |
| Safety Standard             | IEC 60598-1 |
| Electrical Class            | I           |
| IP rating                   | 65          |
| EMC                         | /           |
| EMF                         | /           |
| EMI                         | /           |
| Length                      | 75          |
| Width                       | 50          |
| Height                      | 1000        |
| Weight                      |             |
| Dimming                     | No          |
| Main Color of the luminaire | Grey        |
| Color impact code (IK)      | 04          |

### Product Benefits

- Visual comfort with maximum energy saving.
- Minimalist design with optimum performance.
- Quick & simple installation.
- Flexible deployment options with a wide spectrum of applications.



## GREY

Model No:wwl-100cm-36w-SG-RGB

### LINEAR WALL WASHER LIGHT

Compact & Minimalist linear surface mounted luminaire designed for wall, ceiling & floor mount application. Ideal light distribution serves both wall washing & wall grazing applications.