

INFRARED MOTION SENSOR

600 W

RECESSED

WHITE

- It is recommended to install it at a height of 1.8-4 meters.
- Easy to install.
- Electric power saver.
- Suitable for home and commercial use.
- It is used as a lighting sensor in ceilings and entrance halls.

- For switching lighting systems that depend on brightness and movement.
- For semiautomatic and fully automatic operation.
- Additional activation/deactivation possibility through pushbutton input.
- Detection range (for installation height of 4 m), circular, up to 8 m in diameter.
- Adaptation of the detection range possible using the included masking elements.
- With brightness-independent test mode for evaluating the detection zone.


- With detection display in test mode.
- Ceiling installation using integrated spring bracket.
- Rated voltage: 220-240V~, +10 % / -10 %
- Rated frequency: 50/60 Hz
- Suitable for: 230 V incandescent lamps

- Rated power: **600 W**
- Suitable for: Energy-saving bulbs
- Suitable for: Fluorescent lamps
- Rated current: 4 AX, cos ϕ 0.5
- Protection class (Device): IP 20

- Temperature range (Device): -20 °C - +40 °C
- Detection angle: 360 °
- Dimensions: (L x W x D): 100 mm x 100 mm x 49 mm
- Mounting depth: 44 mm
- Mounting height: - 1.8 m - 4 m



Photometric curve



UP : UNLIMITED

DOWN : <10 LUX



Areas of application

Suitable for – indoor applications

- Offices
- Corridors
- Stairways
- Residential interiors
- Commercial buildings



infrared sensor 360°



mounting height max. 4 m



max. ø 24 m



Presence Ø 7,5 m



2 - 1000 lux



IP20