


ITEM NO : 107392

120P

| caption                     | the value |
|-----------------------------|-----------|
| Rated wattage               | 8.5 W/m   |
| Rated current               | 2.5 A     |
| Rated voltage               | 220-240V  |
| Frequency                   | 50/60 Hz  |
| Power Factor                | ≥ 0.9     |
| Rated lumens                | 750 Lm/m  |
| Efficiency                  | 88.2 Lm/w |
| Lumen Maintenance           | 6000h     |
| Beam Angle                  | >120 °    |
| Color temperature           | 2700 k    |
| Consistency sdcn            | <3        |
| CRI                         | > 80      |
| Rated Lifetime              | 15000 h   |
| Switch cycle                | 7500      |
| Ta                          | 40 °c     |
| Safety Standard             | IEC 60598 |
| Electrical Class            | II        |
| IP rating                   | 65        |
| CHIP QTY/M                  | 120       |
| EMF                         | /         |
| EMI                         | /         |
| Cutout                      | 100 mm    |
| Width                       | 4 mm      |
| Height                      | 10 mm     |
| Roll Length                 | 50 M      |
| Dimming                     | No        |
| Main Color of the luminaire | clear     |
| Color impact code (IK)      | 08        |

## Areas of application

- General indoor illumination
- General outdoor illumination
- Decorative illumination
- Private living areas




## Super protection:

It is made of very safe materials, so it is environmentally friendly  
Provides flexibility in installation and easy of installation



## Product benefits

- Great scope of design options due to long and flexible LED strips
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Suitable for use in damp conditions thanks to high type of protection
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides



Minimum cut size  
100mm

