


ITEM NO : 107420

120P

caption	the value
Rated wattage	10 W/m
Rated current	2.24 A
Rated voltage	220-240V
Frequency	50/60 Hz
Power Factor	≥ 0.9
Rated lumens	500 Lm/m
Efficiency	50 Lm/w
Lumen Maintenance	6000h
Beam Angle	120 °
Color temperature	4000 k
Consistency sdcm	<3
CRI	> 70
Rated Lifetime	15000 h
Switch cycle	7500
Ta	40 °c
Safety Standard	IEC 60598
Electrical Class	II
IP rating	65
CHIP QTY/M	120
Width	15 mm
Height	15 mm
Roll Length	50 M
Dimming	Yes
Main Color of the luminaire	White
Color impact code (IK)	08

Areas of application

- General indoor illumination
- General outdoor illumination
- Decorative illumination
- Private living areas




Super protection:

It is made of very safe materials, so it is environmentally friendly
Provides flexibility in installation and easy of installation



Product benefits

- Great scope of design options due to long and flexible LED strips
- Easy mounting on many smooth surfaces thanks to self-adhesive tape
- Suitable for use in damp conditions thanks to high type of protection
- Maximum flexibility due to large range of accessories
- Simple connection thanks to integrated cables on both sides



Minimum cut size
20 cm