

HUMAN PRESENCE SENSOR WITH BREATHING DETECTION

2000W RECESSED

WHITE


- It is recommended to install it at a height of 2-4 meters.
- With detection display in test mode.
- Ceiling installation using integrated spring bracket.
- Rated voltage: 110-240V~, +10 % / -10 %
- Rated frequency: 50/60 Hz
- Suitable for: 230 V incandescent lamps
- Rated power: **2000W**
- Rated Load: Max.
 - 2000W (220-240V/AC)
 - 1000W (110-130V/AC)
 - 1000W (220-240V/AC)
 - 500W (110-130V/AC)
- Suitable for: Energy-saving bulbs
- Suitable for: Fluorescent lamps
- Protection class (Device): IP 65
- Temperature range (Device): -20 °C - +40 °C
- Detection angle: 360 °
- Dimensions: (L x W x D): 70 mm x 57 mm x 75 mm
- Mounting height: 2-4 m



- For switching lighting systems that depend on brightness and movement.
- Easy to install.
- Electric power saver.
- Suitable for home and commercial use.
- It is used as a lighting sensor in ceilings and entrance halls.
- For semiautomatic and fully automatic operation. Additional activation/deactivation possibility through pushbutton input.
- Detection range (for installation height of 4 m), circular, up to 6 m in diameter.
- Adaptation of the detection range possible using the included masking elements.
- With brightness-independent test mode for evaluating the detection zone.



Photometric curve



Areas of application

- Suitable for – indoor applications
- Offices
 - Corridors
 - Stairways
 - Residential interiors
 - Commercial buildings

