

MODEL NO: LT-42007FD

6500K

Caption	The value
Input Power	3 W
Discharge Power	6 W
Battery current	4500 mAh
Charging Time	<20H/220V
Rated voltage	220-240 V
Frequency	50/60Hz
LED QTY	48Pc
Min. lumens	500 Lm
Max. lumens	1000 Lm
Lumen Maintenance	6000 h
Beam Angle	120°
Color temperature	6500 k
Consistency sdcm	<6
CRI	>70
Rated Lifetime Lighting	17000 h
Rated Lifetime Battery	8000 h
Working Time (6W)	300 Min.
Working Time (3W)	480 Min.
Ta	0 ~ 40 °c
Humidity	10% ~ 80% R.H.
SMD	2835
Safety Standard	IEC 60598
Electrical Class	II
IP rating	20
Lenght	251.7 mm
Width	63.4 mm
Height	255.4 mm
Weight	1.165 Kg
Dimming	No
Main Color of the luminaire	White
Color impact code (IK)	02

Product Description:

Emergency light equipped with two 360° rotatable LED heads, providing high flexibility in directing illumination as needed. It operates automatically during power outages using a rechargeable battery that charges automatically, with indicators for charging and power status. Its durable and lightweight design makes it suitable for corridors, residential buildings, and commercial facilities.



Features:

- Two 360° rotatable LED heads for full directional lighting.
- Automatic rechargeable battery with Charge / Power indicators.
- TEST button for easy functionality check.
- Automatic operation during power failure.
- Durable and lightweight housing for easy installation and use.

Warranty:

- **Emergency Light Warranty:** 2 Years
- **Battery Warranty:** 1 Year