



| DESCRIPTION                        | DETAILS                                                |
|------------------------------------|--------------------------------------------------------|
| Product Description                | NEWPOWER SIZE 7X7<br><b>1GANG 2WAY 16A WIDE SWITCH</b> |
| Item Code                          | <b>206086</b>                                          |
| Standard                           | IEC60669-1:2017                                        |
| Rated Current                      | 16A max                                                |
| Rated Voltage                      | 250V AC                                                |
| Frequency                          | 50 / 60 Hz                                             |
| Product Dimensions                 | 86 x 86 x 31 mm                                        |
| Accessories                        | Mounting screws - 2 x M3.5                             |
| Mounting                           | Flush Mounting                                         |
| Fixing Center                      | 80 mm                                                  |
| Auxiliary fixing options           | 4 Corners                                              |
| Mounting box size                  | 35 mm                                                  |
| Actuating member                   | Rocker                                                 |
| Endurance                          | 40,000                                                 |
| Enclosure Material                 | PC                                                     |
| Contact material                   | Copper                                                 |
| Terminal for current carrying part | Phosphor copper 90-92%                                 |
| Screw terminal                     | Steel                                                  |
| Terminal Identifier                | COM, L1, L2                                            |
| Conductor size                     | 4mm <sup>2</sup>                                       |
| Terminal Capacity                  | 4 x 2.5 mm <sup>2</sup><br>3 x 4 mm <sup>2</sup>       |
| Tightening torque                  | 1.2 Nm                                                 |
| Screw size                         | M4                                                     |



**New Terminal Design:**  
The new saddle-shaped terminal locks the wire without damage, and the screws never come off.

Pattern No.:6  
SBL : 200W

#### WIRING DIAGRAMS

