

PRESENCE SENSORS (MIR)

1200W

SURFACE

WHITE

- It is recommended to install it at a height of 1.8-2.5 meters.
- With detection display in test mode.
- Ceiling installation using integrated spring bracket.
- Rated voltage: 220-240V~, +10 % / -10 %
- Rated frequency: 50/60 Hz
- Suitable for: 230 V incandescent lamps
- Rated power: **0.5W**
- Time Delay: Min.10sec±3sec
- Rated Load: Max.

1200W - 600W (220-240V/AC)

- Suitable for: Energy-saving bulbs
- Suitable for: Fluorescent lamps
- Protection class (Device): IP 44
- Temperature range (Device): -20 °C - +40 °C
- Detection angle: 180 °
- Dimensions: (L x W x D): 86 mm x 60 mm x 95 mm
- Mounting depth: 60 mm
- Mounting height: 1.8-2.5 m
- Detection Distance: 12m max(<24°C)
- Detection Moving Speed: 0.6-1.5m




- For switching lighting systems that depend on brightness and movement.
- Easy to install.
- Electric power saver.
- Suitable for home and commercial use.
- It is used as a lighting sensor in ceilings and entrance halls.
- For semiautomatic and fully automatic operation. Additional activation/deactivation possibility through pushbutton input.
- Detection range (for installation height of 2.5 m), circular, up to 12 m in diameter.
- Adaptation of the detection range possible using the included masking elements.
- With brightness-independent test mode for evaluating the detection zone.

Areas of application


Suitable for – indoor applications

- Offices
- Corridors
- Stairways
- Residential interiors
- Commercial buildings

SENSOR INFORMATION:



Height of installation: 1.8-2.5m



Detection Distance: Max.12m

NEWPOWER®

WALL MOTION SENSOR

حساس حركة جداري



DETECTION RANGE: 180°

مجال التغطية

MODEL NO: NP-122

رقم الموديل

ITEM NO: 201217

رقم الصنف

WHITE
أبيض